



Jumper Wire

Jumper Wire

Jumper wire consists of tinned solid copper conductors with PVC insulation. Single paired or multi-conductor configurations are available for use in distribution frame wiring. Jumper wire has a minimum 3 twists per foot. Tight twist jumper wire has a minimum 12 twists per foot and is Category 5 compatible.

PREMIER[®]

Jumper Wire

Item No.	Mfg. Part No.	Description
3112297500	PT-JW222-RD/WH-S500	2 Conductor 22 Gauge 500 Foot Spool RD/WH
3112427500	PT-JW222-BL/WH-S1000	2 Conductor 22 Gauge 1000 Foot Spool BL/WH
3111237500	PT-JW222-BK/WH-S1000	2 Conductor 22 Gauge 1000 Foot Spool BK/WH
0000125797	PT-JW222-WH-OR-S1000	2 Conductor 22 Gauge 1000 Foot Spool WH/OR
0000125798	PT-JW222-WH-RD-S1000	2 Conductor 22 Gauge 1000 Foot Spool WH/RD
0000032913	PT-JW222-BK/WH-C3000	2 Conductor 22 Gauge 3000 Foot Coil BK/WH
0000015520	PT-JW222-BL/WH-C3000	2 Conductor 22 Gauge 3000 Foot Coil BL/WH
3111117500	PT-JW222-GN/WH-C3000	2 Conductor 22 Gauge 3000 Foot Coil GN/WH
3110077500	PT-JW222-OR/WH-C3000	2 Conductor 22 Gauge 3000 Foot Coil OR/WH
0000032914	PT-JW222-RD/WH-C3000	2 Conductor 22 Gauge 3000 Foot Coil RD/WH
0000112883	PT-JW222-O/BLU-C3000	2 Conductor 22 Gauge 3000 Foot Coil OR/BLU
3112197500	PT-JW222-BK/WH-S5000	2 Conductor 22 Gauge 5000 Foot Spool BK/WH
3112217500	PT-JW222-RD/WH-S5000	2 Conductor 22 Gauge 5000 Foot Spool RD/WH
3111617500	PT-JW422-WH/BL/RD/BK-S2300	4 Conductor 22 Gauge 2300 Foot Spool WH/BL/RD/BK
0000085301	PT-JW1P22-RD/BL-S1000	1 Pair 22 Gauge 1000 Foot Spool Tight Twist RD/BL
0000084317	PT-JW1P22-RD/BL-C3000	1 Pair 22 Gauge 3000 Foot Coil Tight Twist RD/BL
0000288118	2113150	1 Pair 22 Gauge 1000 Foot Spool Tight Twist BL/VI
0000277850	2113185	1 Pair 22 Gauge 3000 Coil Tight Twist BL/VI
0000089145	PT-JW2P22-RD/BL-OR/RD-S1000	2 Pair 22 Gauge 1000 Foot Spool Tight Twist RD/BL OR/RD
0000035794	PT-JW2P22-BL/WH-RD/GN-C1500	2 Pair 22 Gauge 1500 Foot Coil BL/WH RD/GN
0000084318	PT-JW2P22-RD/BL-OR/RD-C1500	2 Pair 22 Gauge 1500 Foot Coil Tight Twist RD/BL OR/RD
3120047500	PT-JW224-BK/WH-S1000	2 Conductor 24 Gauge 1000 Foot Spool BK/WH
0000051881	PT-JW224-BL/WH-S1000	2 Conductor 24 Gauge 1000 Foot Spool BL/WH
0000015516	PT-JW224-GN/WH-S1000	2 Conductor 24 Gauge 1000 Foot Spool GN/WH
0000015526	PT-JW224-RD/BK-S1000	2 Conductor 24 Gauge 1000 Foot Spool RD/BK
3120597500	PT-JW224-RD/WH-S1000	2 Conductor 24 Gauge 1000 Foot Spool RD/WH
0000015522	PT-JW224-BL/WH-C5000	2 Conductor 24 Gauge 5000 Foot Coil BL/WH
3120637500	PT-JW224-BL/YL-C5000	2 Conductor 24 Gauge 5000 Foot Coil BL/YL
3120027500	PT-JW224-BK/WH-S6000	2 Conductor 24 Gauge 6000 Foot Spool BK/WH
3120567500	PT-JW224-RD/WH-S6000	2 Conductor 24 Gauge 6000 Foot Spool RD/WH
3120577500	PT-JW324-RD/WH/BK-S4000	3 Conductor 24 Gauge 4000 Foot Spool RD/BK/WH
3120587500	PT-JW424-RD/WH/GN/BK-S3300	4 Conductor 24 Gauge 3300 Foot Spool RD/WH/GN/BK
0000049311	PT-JW524-BL/OR/GN/BR/SL-C1000	5 Conductor 24 Gauge 1000 Foot Coil BL/OR/GN/BR/SL
0000364781	2113182	1 Pair 24 Gauge 600 Foot Spool BL/VI
3120097500	PT-JW2P24-RD/WH-GN/BK-S3300	2 Pair 24 Gauge 3300 Foot Spool RD/WH GN/BK

Cross Connect Wire



Cross Connect Wire

Cross-Connect Wire

Cross connect wire consists of solid, bare copper conductors with PVC insulation. The conductors are band marked with the color of the paired wires. Cross connect wire is designed for use in cross connecting apparatus in residential, commercial, and industrial applications. Cross connect wire has a minimum 2 twists per foot. Type F and Type H cross connect wire has a minimum 3 twists per foot. Tight twist cross connect wire has a minimum 12 twists per foot and is Category 5 compatible.

PREMIER®

Item No.	Mfg. Part No.	Description
0000282619	2113057	1 Pair 22 Gauge 400 Foot Spool VI/WH
0000284692	2113059	1 Pair 22 Gauge 400 Foot Spool RD/WH
3140207500	XC-1P24-F-VI/BL-S500	1 Pair 24 Gauge 500 Foot Spool Tight Twist VI-BL
3140117500	PT-XC-1P24-BL/WH-S1000	1 Pair 24 Gauge 1000 Foot Spool BL-WH
3140237500	XC-1P24-GN/WH-S1000	1 Pair 24 Gauge 1000 Foot Spool GN-WH
3140247500	XC-1P24-OR/WH-S1000	1 Pair 24 Gauge 1000 Foot Spool OR-WH
3140007500	PT-XC-1P24-VI/WH-1000	1 Pair 24 Gauge 1000 Foot Spool VI-WH
0000015530	XC-1P24-F-WH/BL-S1000	1 Pair 24 Gauge 1000 Foot Spool Type F BL-WH
3140157500	XC-1P24-F-RD/WH-S1000	1 Pair 24 Gauge 1000 Foot Spool Type F RD-WH
0000238666	XC-1P24-F-B/Y-S1000	1 Pair 24 Gauge 1000 Foot Spool Type F BL-YL
0000015532	XC-1P24-OR/WH-S400	1 Pair 24 Gauge 400 Foot Spool Type H Tinned OR-WH
0000106048	PT-JW224-H-OR/WH-S800	1 Pair 24 Gauge 800 Foot Spool Type H Tinned OR-WH
3140067500	PT-XC-2P24-BL/WH-OR/WH-S1000	2 Pair 24 Gauge 1000 Foot Spool BL-WH OR-WH
3140177500	XC-2P24-F-BL/RD-OR/RD-S1150	2 Pair 24 Gauge 1150 Foot Spool Type F BL-RD OR-RD
3140277500	XC-2.5P24-BL/WH-OR/WH-GN-S1000	2.5 Pair 24 Gauge 1000 Foot Spool Tinned BL-WH OR-WH GN
3140127500	PT-XC-3P24-BL/WH-OR/WH-GN/WH-S1000	3 Pair 24 Gauge 1000 Foot Spool BL-WH OR-WH GN-WH
0000057878	PT-XC-1P24-500-RD-YL	1 Pair 24 Gauge 500 Foot Spool Tight Twist RD-YL

600 New Century Parkway
New Century, Kansas 66031-8000
1.800.755.1950

dependonpremier.com