

PREMIER® Bells

Loud ringing bells have a non-magnetic aluminum housing that protects two 6-inch gongs from all types of weather and environments. A mounting bracket is attached.

• Hard-wired telephone connections

Loud Extension Bell

PREMIER

Bells

Item No.	Mfg. Part No.	Description	Voltage Range	Frequency Range	Dimensions
4810317501	PT-101	Loud Extension Bell 95 dB 5900 Ohm Black	55 - 130 VAC	17 - 33 Hz	12.4"L x 5.4"W x 7.5"H
4810327501	PT-102	Loud Extension Bell 95 dB 1000/2650 Ohm Black	55 - 130 VAC	17 - 33 Hz	12.4"L x 5.4"W x 7.5"H



PREMIER Bells

Loud ringing bells are constructed with a highly durable plastic housing for indoor or outdoor use. It operates on telephone ringing voltage. This bell can be mounted on most flat surfaces. A water-tight plastic cover protects the ringer mechanism.

· Hard-wired telephone connections

PREMIER

Item No.	Mfg. Part No.	Description	Voltage Range	Frequency Range	Dimensions
4812417501	PT-75BA	Loud Ringing Bell 95 dB 1000/2650 Ohm Black	55 - 130 VAC	17 - 33 Hz	9.8"L x 5.2"W x 5.3"H

600 New Century Parkway New Century, Kansas 66031-8000 1.800.755.1950

dependonpremier.com